

275 card personalization system

Simple, affordable plastic card personalization

Too often, budget limitations prevent hospitals like yours from taking advantage of new technologies that offer cost-saving or business-building advantages. We understand this dilemma—and that's why we offer the value-priced MedAssure™ 275 card personalization system.

The MedAssure 275 offers fast, quiet and reliable embossing for a new low price—giving you affordability and authentic MedAssure performance in a single, compact package. Finally, healthcare providers on even the thinnest of budgets can justify the cost of plastic card technology.

Standard Features

- 93-character embossing wheel
- Dual operating mode (online or offline)
- Error checking software with auto recovery
- Automatic card counting; two card counters
- RS-232 communications
- 2-line by 40-character message display
- Nine stored formats
- Password Access
- Microsoft® Windows® print driver
- Security keylock on system cabinet

Options

- Pop-up keyboard
- Detached typewriter-style keyboard
- Wristband/label printer
- Printer interface
- 327X or 5256 internal communication interface
- Automatic card feed
- 200-card input hopper
- User prompts in language of choice
- CRT/keyboard
- Data conversion utility software
- CR-80 or CR-50 card capability

Specifications

Physical dimensions:

- With output hopper: 25.0 in. x 17.75 in. x 16.5 in. (635 mm x 451 mm x 412 mm)
- Footprint: 15.0 in. x 14.74 in. (381 mm x 375 mm)
- Weight: 80 lbs. (36.3 kg)
- Embossing speed: Up to 280 cards per hour
- Electrical requirements: 120V, 50/60 Hz

Plastic cards accepted:

- CR-80, .020 in. to .030 in. thickness (.51 mm to .76 mm)
- CR-50, .020 in. to .030 in. thickness (.51 mm to .76 mm)

- UL, CSA and TUV approved
- FCC and CE Mark certified