

295 card personalization system

A powerful, modular patient identification solution

The MedAssure™ 295 card personalization system lets you issue high-quality patient ID cards—with your choice of embossed characters, bar codes, logos, text, personalized smart card chips and encoded magstripes—in a fast, single-pass operation.

This powerful, compact system offers all the card personalization capabilities you need to provide faster service, higher-quality care and stronger marketing programs that can help you win the battle for patient loyalty.

The MedAssure 295 also serves as the base operating platform for MedAssure's new RapidReg™ patient registration solution and the IdentiCare™ patient ID solution. RapidReg can help you increase accuracy and eliminate duplicate records by automating the admitting process. IdentiCare leverages digital imaging technology to help you provide better patient care—and maximize uncompensated care reimbursement.

Standard Features

- 93-character embossing wheel
- Dual operating mode (online or offline)
- Error checking software with auto recovery
- Automatic card counting; two card counters
- RS-232 communications
- 2-line by 40-character message display
- Nine stored formats
- Password Access
- Field-upgradable
- Security keylock on system cabinet

Options

- 327X or 5256 internal communication interface
- Drivers for Windows® 3.1, 95 or NT
- Printer interface
- Pop-up keyboard
- Detached keyboard-style keyboard
- CRT/keyboard
- CR-80 or CR-50 card capability
- Automatic card feed
- 200-card input hopper
- Security keylock on input hopper
- Variety of card output configurations
- UltraGrafix® print module
- Magnetic stripe encoding module
- Color topping module
- Smart card personalization module
- Indent printing
- Data conversion utility software
- Wristband/label printer

- QuikWorks® image capture/card design software
- User prompts in language of choice

Specifications

Physical dimensions:

- With output hopper: 25.0 in. x 17.75 in. x 16.5 in. (635 mm x 451 mm x 412 mm)
- With topper module: 25.25 in. x 17.75 in. x 16.5 in. (641 mm x 451 mm x 412 mm)
- With extended cabinet and output hopper: 31.25 in. x 19.54 in. x 16.5 in. (794 mm x 497 mm x 412 mm)
- Footprint: 15.0 in. x 14.74 in. (381 mm x 375 mm)
- Footprint with topper module: 19.75 in. x 15.5 in. (502 mm x 394 mm)
- Footprint with extended cabinet: 21.25 in. x 14.75 in. (540 mm x 375 mm)
- Weight: 80 lbs. (36.3 kg) With topper: 123 lbs. (55.8 kg) With extended cabinet: 111 lbs. (50.4 kg)
- Embossing speed: Up to 380 cards per hour
- Electrical requirements:
 - 120V, 50/60 Hz • 240V, 50/60 Hz
- Plastic cards accepted:
 - CR-80, .020 in. to .030 in. thickness (.51 mm to .76 mm)
 - CR-50, .020 in. to .030 in. thickness (.51 mm to .76 mm)
- UL, CSA and TUV approved
- FCC and CE Mark certified